



DSUB6F68 Director Collection

The Director DSUB6F68 delivers awe-inspiring bass from the ceiling, performance you would expect from a floor-standing subwoofer. The Dual-6" Woofer design of the bandpass enclosure keeps vibration under control while producing the lowest of lows with a passive crossover. Designed with the same finished aesthetic as Director 6 and 8" speakers, the DSUB6 brings powerful bass with impact to an in-ceiling listening experience.



DSUB6F68

Clean, Powerful Bass

Only audible worthy bass frequencies pass through the port of the DSUB6 from the bandpass to deliver a powerful listening experience. This ensures power is strictly utilized in creating the true fidelity low-end output.

Dueling Effort

Two high-density aluminum woofers sit across from one another inside of the subwoofer enclosure. As a result, the output is enhanced while distortion and cabinet vibrations are significantly reduced.

Multi-Finish Options

The DSUB6F3 comes with magnetic bezel-less grilles in both square and round finishes to match perfectly with designer recessed lighting.

Paintable Low Profile Grille

As expected with all Origin Acoustics speakers, the DSUB6 delivers high performance audio while remaining completely concealed from plain sight with a sleek paintable bezel-less magnetic grille.

Passive Crossover

the DSUB6F3 contains a thorough passive crossover that maintains low frequency response while passing off the appropriate mid and high frequencies to the surrounding D38 satellites.

Tool-less Mounting System

The Zip-Cliq[™] secures the speaker in the ceiling with the exact torque to ensure a tight fit. This is accomplished by squeezing the clips into place and locking the speaker with a twist.

Specifications

Model	DSUB6F68
Part Number	DSUB6F680
Woofer Cone	Polypropylene
Woofer Dimensions	6.5 (165mm)
Frequency Response	37Hz - 200 kHz ± 3dB
Impedance	8 ohm
Power Handling	150 Watts
Box Dimensions	7.9 x 11.8 x 18.9" (200 x 300 x 480mm)
Tube Dimensions	29.5" x 6.2" (158 x 750mm)
Grille Diameter	10" (254mm)
Cutout Diameter	8.75" (222mm)
Mounting Depth	7.9" (200mm)



Length



Not to Scale