

## 5" DIRECTOR SERIES



#### **DETAILS MATTER**

The increasing popularity of smaller recessed light openings has created a huge demand for speakers that "line up" with ceiling lighting.

### PRODUCT ID



Designed with Architects and Interior Designers in mind, the Director 5" Series aesthetically matches high-end 6" can lights, while still producing excellent sound quality.

Paired with our matching 5" aperture in-ceiling sub and DSP3-150 Amplifier, looking good has never sounded better.



# RESOUNDING CLARITY

The secret of Origin Acoustics' superior sound staging is our patented Dual Plane Stabilization Diaphragm™ Tweeter technology. This patented tweeter design improves high-frequency performance, prevents distortion and increases loudness.




### 5" DIRECTOR SERIES





SPECIFICATIONS ALL 5" SERIES
Cutout Diameter 5 %" (149mm)
Speaker Diameter 6 13/16" (172mm)
Mounting Depth 3 3/4" (95mm)

Grille Diameter 7 3/16" (183mm)

Grille Depth 3/16" (5mm)







SPECIFICATIONS D59 D57 D57DT/SUR

PartSCD50900Tweeter1" Silk DPSD™ MMP™Woofer5 ¼" Kevlar®Frequency Response40 - 125 WattsPower Handling68Hz-20kHz

6 ohm

SCD50700 1" Silk DPSD<sup>TM</sup> MMP<sup>TM</sup> 5 1/4" Glass Fiber 40 - 125 Watts 69Hz-20kHz 6 ohm SCD2T50700

3/4" Dual Silk DPSD™

5 1/4" Glass Fiber


40 - 125 Watts


69Hz-20kHz


6 ohm


### LINE DRAWINGS

**Impedance** 















D57-59



D57 DT/SUR



Please visit docs.originacoustics.com or scan the QR code using your smart device for the most up to date specifications and use instructions for this product. Products may only be purchased through an authorized integration partner.