



# DBA10 In-Ceiling Subwoofer

The Origin Acoustics in-ceiling subwoofer delivers room-shaking bass while remaining out of sight. As it was developed by the engineers at Origin Acoustics, you know it's reliable and contains only the finest materials. The DBA10 is a 10" fiberglass subwoofer with Butyl Rubber X Wave Surround. Easy install with Origin's tool-less Installation system. The DBA10 is optimized to work with DSP3-100 Amplifiers.

#### Woofer Cone Materials

This patented tweeter has the greatest output and is able to crossover much lower to either the woofer or the midrange improving both dispersion and the frequency response.

## Compression Molded Baskets

These complex baskets that support the woofer cones were computer designed and compression molded with absolute precision allowing for unique support and venting elements to assure peak performance.

### TriLinear® Configuration (TLC)

The three-driver design is efficient and is more precise by dividing the frequency spectrum into smaller segments allowing the individual drivers to concentrate on a more limited sonic palette.

## Tool-Less Mounting System

The Tool-Less Installation secures the speaker in the ceiling with the exact torque to ensure a tight fit. This is accomplished by squeezing the clips into place and locking the speaker with a twist.

## X-Wave<sup>™</sup> Woofer Surround

This suspension element absorbs unwanted frequencies that reflect up and down the woofer cone to reduce harmonic distortion while maintaining the desired linear travel of the woofer.

### EQ Adjustment

These switches on the baffle allows the adjustment of the output of either the high frequencies or both high and low frequencies to custom tailor the sound based on the proximity of the architectural elements of the room.





- Woofer: 10" Fiberglass
- Diameter: 11 1/4" (286mm)
- Grille Diameter: 11 <sup>2</sup>1/<sub>32</sub>" (296mm)
- Frequency Response: 35Hz-Crossover
- Power Handling: 50-175 Watts
- Grille Diameter: 11 <sup>2</sup>1/<sub>32</sub>" (296mm)
- Cutout Diameter: 10 3/8" (264mm)
- Mounting Depth: 6 1/32" (158mm)

